



Epson business projectors are the essential choice for your office with convenient features from wide connectivity options to space-saving designs. Enjoy cost-savings from long lamp-life and maintenance cycles that will benefit your business in the long run. Complete with brilliant colours and quality images, choose Epson for business projectors that meets your needs.



FB-97H/945H/965H





10,000 Hours Lamp Life in Eco Mode







2 x HDMI







3-in-1 Wi-USB Display

EB-955WH

All-in-One Essentials

Enhance your meetings with key features such as flexible placement and versatile connectivity.

Cost-saving Features

Save time and money with 10,000 hours for both lamp-life (in eco-mode) and air filter maintenance cycle.

Stunning Colour Brightness

ENGINEERED FOR BUSINESS

High colour light lumens let you achieve sharp images and dazzling colours that will enhance every presentation.











SEE VIBRANT, REALISTIC COLOURS WITH HIGH COLOUR BRIGHTNESS.




See colours like never before. Epson 3LCD projectors deliver brilliant colours that match its white brightness to give you balanced, realistic, and vibrant images. It's no wonder Epson projectors are the people's preferred choice.



Up to 3X Wider Colour Gamut

Colour gamut refers to the range of colours that can be reproduced by a display device – the wider the gamut, the more realistic it is. Epson 3LCD projectors project three times wider gamut that matches closely to the original standard of a display device (sRGB), as compared to 1-chip projectors.



Comparing the yellow corners among the three gamuts, 1-chip projectors have a distinctly darker and smaller set of colours which are not as vibrant as Epson 3LCD projectors.



Up to 3X Brighter Colours

Epson 3LCD projectors deliver up to three times the colour brightness, effortlessly creating the same colour and white brightness, resulting in faithful images with superior colour balance.





No Rainbow Effect

With 1-chip projectors, the spinning motion of the sequential colour wheels tend to cause colours to break out into distinct red, green and blue. Called the rainbow effect, this may cause users to suffer headaches with prolonged viewing. Epson projectors do not give out this effect, giving users a comfortable experience.







Enjoy easy mobile presentations with Epson's multimedia projector series. Versatile, user-friendly and equipped with advanced features such as wireless transmission, multi-PC projection and HDMI connection, these projectors deliver smooth and high-contrast presentations whenever and wherever you need.



All-in-one Essentials

1.6x Zoom Lens


Enjoy greater placement flexibility with 1.6x zoom lens*. With wider lens, you can position the projector closer to the screen to free up valuable room and desk space.

Narrow zoom ratio

* Applicable on EB-945H/965H/955WH only.

Multi-PC Projection

With the control of a host PC, up to 50 terminals can be connected via the multi-PC projection from a single projector. The host PC acts as a moderator, selecting media from up to four terminals to be projected simultaneously. With the moderator function, you can maintain control and prevent tampering with what's projected on screen.



Wireless Transmission

Enjoy enhanced connectivity and flexibility with Wi-Fi connectivity*. Easily share and transmit images, text and files from your smart devices using the "Epson iProjection" application for smooth and smart projections. And with an additional attachment piece holding the wireless LAN adaptor in place, your transmissions will never be interrupted.



Epson iProjection

The Epson iProjection application enables a wireless connection for projecting images and files from your smart devices. The new "QR Code Reader" function makes this wireless connection even easier by simply reading the QR code that is projected on the screen from your smart devices.




* In iProjection, projector profile search, multi-screen display, distribution function, audio transfer, movie file transfer, interrupt connection disabling and encryption data transfer capabilities are not supported.



Open the iProjection in your smart device

Scan the QR code on the projection screen



Project the contents from your smart device wirelessly on the projection screen

High Contrast Ratio

Add brilliance to your presentations. Boasting stunning brightness of up to 3,500 lumens and a high contrast ratio of 10000:1, these projectors enable you to project beautiful, well-defined images wherever you are, regardless of ambient light.



Horizontal Keystone Adjuster

Deliver powerful presentations anywhere in the room. With the easy-touse sliding Horizontal Keystone Adjuster, screen corrections can be done quickly, easily and accurately, even in a limited space.

With automatic vertical keystone detection and adjustment, there is no longer any need for awkward and time-consuming manual image adjustments that interrupt the smooth flow of your presentation delivery. This handy feature automatically detects the projector's vertical keystone distortion and corrects it instantly.







Wide-ranging Connectivity

Advanced connectivity features mean convenient and hassle-free projections of your presentations. With a wide-ranging interface, you can choose from a variety of connection methods including HDMI, VGA and LAN. In addition, these projectors are equipped with two HDMI ports, one of which is MHL-enabled*, for greater digital compatibility.

Simply connect your MHL-compatible device with the MHL cable to fully enjoy your contents on the big screen. What's more, when connected, you can charge your smart device and operate it using the projector's remote control.







2 HDMI + MHL

Redirected Exhaust

The front-facing exhaust is intelligently positioned to prevent anyone from being exposed to the hot exhaust, especially when on a narrow table. This allows the audience to fully concentrate on the presentation, even if they are seated beside or behind the projector.









Other projectors with side exhaust

^{*} Applicable for EB-97H/945H/955WH/965H only.

Split Screen

Display images from two different sources side by side on the same screen for a more effective presentation. In video conferences, for example, images of presentation materials and remote participants can be shown simultaneously. What's more with Digital x Digital compatibility, you'll enjoy sharper, more vibrant projections.



Superior Sound Quality

The built-in 16W speaker* provides ample sound even in large rooms, removing the need for external speakers to save you valuable time and money.



^{*} Applicable for EB-97H/945H/965H/955WH only.

Easy-to-replace Lamps

With the lamp cap located on the upper side of the projector, you can change lamps easily even if the projector is installed on the ceiling. Lamps can be replaced quickly without tools and dismounting of the projector from the ceiling mount.



Firmware Updates

Easily update your projector's firmware without having to take it to a service centre. To update, simply insert a USB memory stick with the necessary software. Updates can be done over LAN network or via a USB-B connection.





Auto Power On


With the auto power on function, projection starts automatically once a projection signal is detected via VGA cable, providing you with an easy and hassle-free presentation.



Cost-saving Features

Longer Lamp Life

With a long lamp life of 10,000 hours in ecomode, the frequency of costly lamp replacements is reduced, saving you time and money.



Air Filter

With a maintenance cycle of 10,000 hours in eco-mode, the need for regular maintenance of the air filter is minimised to save you time and money.

Eco Features

- Uses just 0.26W of power in standby mode
- Projector optics employ lead-free lenses
- Unpainted plastic housing reduces the environment impact
- The flame retardants used in the plastic housing do not contain chlorine or bromine

Better Products for a Better Future

For more information on Epson's environmental programmes, visit http://global.epson.com/SR/environment.

PARTNERS IN PERFECTION

Wireless LAN Adaptor ELPAP07



Supports 802.11 b/g/n connection

Compatible with all Epson wireless-enabled projectors

Ink Tank System L455



Print speed: 33ppm/cpm Multifunctional: print, scan, copy Seamless connectivity to Wi-Fi, Wi-Fi Direct and Epson Connect



Don't compromise on safety – use Epson genuine lamps to avoid damaging your projector. Eliminate the risk of melting parts of your projector, as well as breaks that result in high-voltage shutdown. With a 0% failure rate even after 2,000 hours of usage – compared to 70% in non-genuine lamps – Epson genuine lamps are safer and more reliable. Choose the best possible viewing experience filled with long-lasting sharpness and colour in every projected image with Epson.





GENUINE EPSON LABEL

To ensure the best quality and safety when using your Epson Projector, look for the "Genuine EPSON Colour Shifting Label" on your projector lamp. Real quality and value, only with Epson genuine supplies.

DANGERS OF NON-GENUINE LAMPS



UNRELIABLE

Counterfeit lamps deteriorate and break much faster than genuine ones.



UNSAFE

Parts of your Epson projector such as the housing or wires may melt, disconnect, or become damaged when using non-genuine lamps.



POOR IMAGE QUALITY

Counterfeit lamps may result in inaccurate colour projection, lower brightness levels, as well as flickering images that spoil your viewing experience.



MODEL NUMBER		EB-97H			
Projection Technology		RGB liquid crystal shutter projection system (3LCD)			
Specifications of					
LCD	Size	0.55" without MLA (D8)			
Native Resolution SVGA		XGA			
Projection Lens Type		Optical Zoom (Manual) / Focus (Manual)			
1 Tojootion Lono	F-Number	1.58 - 1.72			
	Focal Length	16.9 - 20.28 mm			
	Zoom Ratio	1-1.2			
	Throw Ratio	1.48 - 1.77 (Wide - Tele)			
Lomp		200W UHE			
Lamp	Type Life (Normal / Eco) ⁻¹				
Saraan Siza (Dra	. ,	5,000 hours / 10,000 hours			
Screen Size (Projected Distance)		20" 200" [0 90 0 12 m]			
Zoom : Wide		30" - 300" [0.89 - 9.12 m]			
Zoom : Tele		30" - 300" [1.07 - 10.95 m]			
Brightness*2		0.700			
Colour Light Output (Normal)		2,700lm			
White Light Output (Normal)		2,700lm			
Contrast Ratio		10,000.4			
Auto Iris: On		10,000:1			
Video Quality		3D Y/C Separation, Noise Reduction, Motion Compensated Interlace-Progressive Conversion (2-2,3-2 Film Detection)			
Colour Mode	<i></i>	Dynamic, Presentation, Theatre, sRGB, Blackboard			
Internal Speaker	r(s)				
Sound Output		16W Monaural			
Keystone Correct					
Vertical / Horizonta		±30° / ±30° (Slide Bar)			
Auto Keystone Co	prrection	Yes (Vertical)			
Connectivity					
Analog Input	D-Sub 15pin	2 (Blue)			
	Composite	RCA x 1 (Yellow)			
	S-Video	Mini DIN x 1			
Digital Input	HDMI	2 (1 × MHL)			
Audio Input	RCA (White/Red)	1			
	Stereo Mini Jack	2			
Audio Output	Stereo Mini Jack	1			
USB Input	USB Type A	1 (for USB Memory, USB Document Camera, Wireless LAN, Firmware Update)			
	USB Type B	1 (for USB Display, Mouse, K/B, Control, Firmware Update)			
Mic I/O	Stereo Mini Jack	1			
Control I/O	RS-232C	D-Sub 9pin x 1			
Network	Wired LAN	1			
	Wireless LAN	Optional (ELPAP07)			
Wireless Specific	cations				
Supported Speed	For Each Mode ^{*3}	IEEE 802.11b: 11 Mbps, IEEE 802.11g: 54 Mbps, IEEE 802.11n: 130 Mbps			
Wireless LAN Security		WPA-PSK (TKIP/AES) / WPA2-PSK(TKIP/AES)			
Operating Temperature		5 - 35 °C <41 - 95 °F> (20% - 80% Humidity, No Condensation)			
Operating Altitude		0 - 3,000 m <0 - 9,843 ft> (over 1,500m / 4,921ft: with high altitude mode)			
Direct Power On / Off		Yes			
Start-Up Period		5 seconds, Warm-up Period: 30 seconds			
Cool Down Period		Instant Off			
Power Supply Voltage		100 - 240 V AC ±10%, 50/60 Hz			
	otion (220 - 240V)	- 			
Lamp On (Normal / Eco)		287W / 215W			
Standby		0.26W			
	uding Feet (D X W X H)	244 x 297 x 87 mm			
Weight					
Fan Noise (Normal / Eco)		2.7kg 37dB / 29dB			
Warranty	iai / Ecoj				
-		2 years come in			
Main Unit		2 years carry-in			

Supplied Accessories

Power Cable: 1.8m

Computer Cable (VGA Cable): 1.8m Remote Control: Yes, with battery attached

Soft Carrying Case

Optional Accessories

Spare Lamp: ELPLP88 Air Filter: ELPAF32

Wireless LAN Adaptor: ELPAP07

Quick Wireless Connection USB Key: ELPAP09

Ceiling Mount: ELPMB23

EB-97H



©2015 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Projected images shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Dealer's Stamp

Dealer's Stamp

1 Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time.

Information correct at time of printing Printed June 2015

To find out more, visit www.epson.com.my/projectors or call 1800-8-17349 (Toll-free)



Colour brightness (colour light output) and white brightness (white light output) will vary depending on usage conditions. Colour light output measured in accordance with IDMS 15:4; white light output measured in accordance with ISO 21118.

Maximum speed and range is achievable when used with same enhanced mode technology. Actual data rates, features and performance may vary depending on your computer system, the environment and other factors.



MODEL NUMBER		EB-945H	EB-955WH	EB-965H		
Projection Technology		RGB liquid crystal shutter projection	on system (3LCD)			
Specifications o	f Main Parts					
LCD	Size	0.63" with MLA (D7)	0.59" with MLA (D8)	0.63" with MLA (D7)		
	Native Resolution	XGA	WXGA	XGA		
Projection Lens	Type	Optical Zoom (Manual) / Focus (M	fanual)			
	F-Number	1.51 - 1.99				
	Focal Length	18.2 - 29.2 mm				
	Zoom Ratio	1 - 1.6				
	Throw Ratio	1.38 - 2.24 (Wide - Tele)				
Lamp	Туре	200W UHE				
Life (Normal / Eco) ^{*1}		5,000 hours / 10,000 hours				
Screen Size (Pro	jected Distance)	-				
Zoom : Wide		30" - 300" [0.83 - 8.54 m]	33" - 280" [0.97 - 8.45 m]	[30" - 300" [0.83 - 8.54 m]		
Zoom : Tele		30" - 300" [1.36 - 13.86 m]	33" - 280" [1.59 - 13.71 m]	30" - 300" [1.36 - 13.86 m]		
Brightness'2						
Colour Light Output		3,000lm	3,200lm	3,500lm		
White Light Output (Normal / Eco)		3,000lm	3,200lm	3,500lm		
Contrast Ratio						
Auto Iris: On		10,000:1				
Video Quality		3D Y/C Separation, Noise Reduction Motion Compensated Interlace-Progressive Conversion (2-2,3-2 Film Detection				
Colour Mode		Dynamic, Presentation, Theatre, sRGB, Blackboard				
Internal Speaker	r(s)		- ,			
Sound Output	1-7	16W Monaural				
Keystone Correct	ction	- TOTT WORKER				
Vertical / Horizonta		±30° / ±30° (Slide Bar)				
Auto Keystone Correction		Yes (Vertical)				
Connectivity	WI COLLOTT					
Analog Input	D-Sub 15pin	2 (Blue)				
a lalog ii ipat	Composite					
	S-Video	RCA x 1 (Yellow) Mini DIN x 1				
Digital Input	HDMI	2 (1 x MHL)				
		1				
Audio Input	RCA (White/Red)	2				
Audio Outout	Stereo Mini Jack Stereo Mini Jack	1				
Audio Output			ant Camana Miralaga I ANI Firm ware I la	datal		
USB Input	USB Type A		ent Camera, Wireless LAN, Firmware Up	date)		
	USB Type B	1 (for USB Display, Mouse, K/B, C	control, Firmware Update)			
Mic I/O	Stereo Mini Jack	1				
Control I/O RS-232C		D-Sub 9pin x 1				
Network I/O	Wired LAN	1				
	Wireless LAN	Optional (ELPAP07)				
Wireless Specifi						
Supported Speed			2.11g: 54 Mbps, IEEE 802.11n: 130 Mbp	OS		
Wireless LAN Security		WPA-PSK (TKIP/AES) / WPA2-PSK(TKIP/AES)				
Operating Temperature		5 - 35 °C <41 - 95 °F> (20% - 80% Humidity, No Condensation)				
Operating Altitud		0 - 3,000 m <0 - 9,843 ft> (over 1,500m / 4,921ft: with high altitude mode)				
Direct Power On / Off		Yes				
Start-Up Period		5 seconds, Warm-up Period: 30 seconds				
Cool Down Period		Instant Off				
Power Supply Vo	=	100 - 240 V AC ±10%, 50/60 Hz				
Power Consump	otion (220 - 240V)					
Lamp On (Normal / Eco)		287W / 215W				
Standby		0.26W				
Dimension Excluding Feet (D X W X H)		269 x 297 x 87 mm				
Weight		2.9kg				
Fan Noise (Normal / Eco)		37dB / 29dB				
Warranty						

Supplied Accessories

Power Cable: 1.8m

Computer Cable (VGA Cable): 1.8m Remote Control: Yes, with battery attached

Soft Carrying Case

Optional Accessories

Spare Lamp: ELPLP88 Air Filter: ELPAF32

Wireless LAN Adaptor: ELPAP07

Quick Wireless Connection USB Key: ELPAP09

Ceiling Mount: ELPMB23

EB-945H / EB-955WH / EB-965H



©2015 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Projected images shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Dealer's Stamp

Information correct at time of printing Printed June 2015

1 Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time.

Colour brightness (colour light output) and white brightness (white light output) will vary depending on usage conditions. Colour light output measured in accordance with IDMS 15:4; white light output measured in accordance with ISO 21118.

Maximum speed and range is achievable when used with same enhanced mode technology. Actual data rates, features and performance may vary depending on your computer system, the environment and other factors.



To find out more, visit www.epson.com.my/projectors or call 1800-8-17349 (Toll-free)

