EB-Z11000W



Featuring an impressive 11,000 lumens, WXGA resolution and 3LCD technology, the EB-Z11000W is ideal for large venues and simple to set up.

With 11,000 lumens brightness and WXGA resolution, the white EB-Z11000W is an impressive and versatile installation projector. Able to project portrait aspect images for digital signage, the EB-Z11000W has a flexible installation angle, lens shift for off-centre positioning and plenty of calibration options, with optional Wi-Fi and HDBaseT connectivity.

Clear images and 3LCD technology

The 11,000-lumen EB-Z11000W is an ultra-bright WXGA-resolution projector, benefiting from Epson's 3LCD technology, which ensures high-quality images with equally high White and Colour Light Output for vivid colours and bright images, even in daylight, and three times brighter colours than competitive projectors¹.

Perfect for large venues

Museums, auditoriums and corporate environments can benefit from the EB-Z11000W's large projected image, ideal for making a big impact.

Portrait projection

Able to project portrait aspect images, the EB-Z11000W is ideal for digital signage. Welcome to a whole new way of seeing things; portrait mode is also useful when a venue or event, such a fashion show, doesn't lend itself to landscape projection.

Easy set-up

As well as a flexible installation angle and lens shift for off-centre positioning, the EB-Z11000W includes plenty of calibration options such as edge blending, test patterns and Epson's Super Resolution feature.

Connectivity

The EB-Z11000W includes HDBaseT, which allows up to five connections in one. Optional Wi-Fi is also included for extra flexibility.

Short-throw capability

Great news for auditoriums and lecture theatres; a new and exclusive LU02 short throw lens allows this projector to be positioned closer to the screen.

KEY FEATURES

High-brightness
 A stunning 11,000 lumens of brightness
 Elovible

15,000:1

10m

11000 In

IDBase^{*}

- Flexible
- Choose different installation angles • 3LCD technology
- For vivid colours and bright images
- Connectivity

HDBaseT and optional Wi-Fi connectivity • Portrait projection

When landscape isn't suitable





PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	1.03 inch with C2 Fine
IMAGE	
Colour Light Output	11,000 lumen- 7,100 lumen (economy)
White Light Output	11,000 lumen - 7,100 lumen (economy)
Portrait Colour Light Output	8,100 lm
Portrait White Light Output	8,100 lm
Resolution	WXGA, 1280 x 800, 16:10
Contrast Ratio	15,000 : 1
Lamp	380 W, 2,000 h durability, 4,000 h durability (economy mode)
Lamp (portrait mode)	304 W, 1,000 Hours Durability
Keystone Correction	Manual vertical: ± 30 °, Manual horizontal ± 30 °
Aspect Ratio	16:10
OPTICAL	
Projection Ratio	1.57 - 2.56:1
Zoom	Motorized, Factor: 1 - 1.61
Lens Shift	Motorized - Vertical ± 60 %, horizontal ± 18 %
Projection Size	60 inches - 500 inches
Projection Lens F Number	1.65 - 2.51
Focal Distance	36 mm - 57.5 mm
Focus	Motorized
Projection Distance Wide	2 m - 17.2 m
	3.3 m - 27.8 m
Projection Distance Tele	
Lens	Optical
CONNECTIVITY	
Interfaces	USB 1.1 Type A, USB 2.0 Type B (Service Only), RS-232C, WLAN, VGA in, VGA out, DVI in,
	HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT
GENERAL	
Energy Use	1,060 W, 788 W (economy), 0.37 W (standby)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	741 x 534 x 197 mm (Width x Depth x Height)
Product weight	26 kg
Noise Level	Normal: 40 dB (A) - Economy: 35 dB (A)
Temperature	Storage -10° C - 60° C
Humidity	Operation 20% - 80%, Storage 10% - 90%
Included Software	EasyMP Monitor, EasyMP Multi PC Projection, EasyMP Network Projection
Options	Document camera
ADVANCED FEATURES	
Security	Kensington lock, Security cable hole
Video Colour Modes	Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM
OTHER	06 mantha Carra in ar 00.000 h Laws 10 mantha ar 1.000 h
Warranty	36 months Carry in or 20,000 h, Lamp: 12 months or 1,000 h
	Optional warranty extension available

EB-Z11000W

WHAT'S IN THE BOX

- VGA cable
- HDMI Cable Clamp
- Power cable
- Remote control incl. batteries
- User's Manual Set



OPTIONAL ACCESSORIES

- Lamp ELPLP81
 V13H010L81
- 3D Polarizer ELPPL01 V12H618A01
- Ceiling Mount (Low) ELPMB25 V12H003B25
- Ceiling Mount (High) ELPMB26 V12H003B26
- HDBaseT Transmitter ELPHD01 V12H547041
- 3D Glasses (Passive for Child, x5) ELPGS02B V12H541B10
- Quick Wireless Connect USB key ELPAP09 V12H005M09
- Lamp (x2) ELPLP82
 V13H010L82
- Lamp (Portrait, x1) ELPLP83 V13H010L83

OPTIONAL LENSES

- Lens (ST Off Axis) ELPLU02 V12H004U02
- Lens (Long Throw) ELPLL07 V12H004L07
- Lens (Middle Throw 1) ELPLM06 V12H004M06
- Lens (Middle Throw 2) ELPLM07 V12H004M07
- Lens (Rear Wide) ELPLR04 V12H004R04
- Lens (Wide) ELPLW04
- V12H004W04

LOGISTICS INFORMATION

SKU	V11H608040
EAN code	8715946541259
Multiple Order Quantity	1 Units
Country of Origin	China
Pallet Size Euro	4 Units
Pallet Size Block	4 Units

For more information please contact:

Telephone: 01952 607111 (UK)+ 01 436 7742 (Republic of Ireland) E-mail: enquiries@epson.co.uk Chat: etalk.epson-europe.com Fax: 0871 222 6740 + Local call rate.

Web: www.epson.co.uk www.epson.ie 1. Compared to leading 1-chip DLP business and education projectors based on NPD data, July 2011 through June 2012. Colour brightness (Colour Light Output) measured in accordance with IDMS 15.4. Colour brightness will vary depending on usage conditions. For more information please visit www.epson.eu/CLO

EB-Z11000W





Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.