

SKU	USB to DC Cable	USB 1 or 2
AT-HD4-V40SRS	AT-PWUSB-L	1 USB
AT-HD4-SI40SR	AT-PWUSB-L	1 USB
AT-HDSync	AT-PWUSB-L	1 USB
AT-DVISync	AT-PWUSB-L	1 USB
AT-DVI40SRS	AT-PWUSB-L	1 USB
AT-HD-V40SRS	AT-PWUSB-L	1 USB
AT-HD-BIR40SR	AT-PWUSB-L	1 USB
AT-HDRP	AT-PWUSB-L	1 USB
AT-HDRS	AT-PWUSB-L	1 USB
AT-HD-3GSDI	AT-PWUSB-L	2 USB
AT-SDI10SR-LC	AT-PWUSB-L	2 USB
AT-HD50SS	AT-PWUSB-L	2 USB
AT-HD50RSL	AT-PWUSB-L	2 USB
AT-HD-RG100SR	AT-PWUSB-L	2 USB
AT-3GSDI-HD	AT-PWUSB-L	2 USB
HD4-V110SR	AT-PWUSB-L	2 USB

*1 USB - The AT-PWUSB-L has 2 USB connectors on one side and a DC power connector on the other side.
If the required Wattage is below 2.5W per device, 1 USB can be used and if < 5Watts, 2 USB's will be required