

DIGITAL PROJECTOR | TH670




Features

- Full 1080p (1920x1080) resolution
- 3,000 ANSI lumens
- 10,000:1 high contrast ratio
- HDMI
- 10W speaker
- <0.5W standby mode



Input and Output Terminals



- | | |
|---------------------------------|---------------------|
| 1 Audio in/out (Mini Jack) | 6 RS232 (DB-9pin) |
| 2 Audio L/R in (RCA) | 7 USB (Type A) |
| 3 Composite Video in (RCA) | 8 USB (Type Mini B) |
| 4 Computer in 1/2 (D-sub 15pin) | 9 Microphone |
| 5 HDMI | |

Specifications

Projection System	DLP®
Native Resolution	1080p (1920 x 1080)
Brightness	3,000AL
Contrast Ratio	10,000:1
Display Color	1.07 Billion Colors
Lens	F=2.55~2.76, f=22.3~26.76
Aspect Ratio	Native 16:9 (5 aspect ratio selectable)
Throw Ratio	1.5~1.8 (62"±3% @ 2m)
Image Size (Clear Focus/ Maximum)	60"~120" / 300"
Zoom Ratio	1.2:1
Lamp Type	210W
Lamp (Normal/Eco/SmartEco Mode)	4000/6000/10000 hours
Keystone Adjustment	1D, Vertical +/- 30 degrees
Projection Offset	116% ±2.5% (Full Image Height Standard)
Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200) RB=reduced blanking
Horizontal Frequency	15~102KHz
Vertical Scan Rate	24~120Hz
Compatibility	HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p Video Compatibility: NTSC, PAL, SECAM 3D Compatibility: Frame Sequential: Up to 60Hz 720p Frame Packing: Up to 24 Hz 1080p Side by Side: Up to 24Hz 1080p Top Bottom: Up to 60Hz 1080p
Interface	Computer in (D-sub 15pin) x 2 (Shared with component) Composite Video in (RCA) x 1 HDMI x 1 Audio in (Mini Jack) x 1 Audio L/R in (RCA) x 1 Audio out (Mini Jack) x 1 Microphone in x 1 Speaker 10W x 1 USB (Type mini B) x 1 (Download) USB (Type A) x1 (1.5A power supply) RS232 (DB-9pin) x 1 IR Receiver x 1 (Front)
Dimensions (WxHxD)	12.8" x 9.17" x 5.39" (327 x 233 x 137mm)
Weight	6.61 lbs / 3.0kg
Power Supply	AC100 to 240 V, 50 to 60 Hz
Power Consumption	Normal 260W, Eco 210W, Standby <0.5W
Power Management Function	Automatic power off after 20 minutes without a display source
Audible Noise	31/29 dBA (Normal/Economic mode)
Languages	(28 Languages)
Picture Mode	**Dynamic / Presentation / sRGB / Cinema / (3D) / User 1 / User 2
Accessories (Standard)	Lens Cover, Remote Control w/ Battery, Power Cord, User Manual CD, Quick Start Guide, Warranty Card, VGA Cable
Accessories (Optional)	Spare Lamp Kit P/N: 5J.JEL05.001 Ceiling Mount P/N: 5J.JAM10.001 3D Glasses P/N: 5J.J9H25.001 Carry bag TBD
UPC / Part #	8400460-3339-2 / 9H.JEL77.33A
Limited Warranty	1 Year Parts/Labor; 1 Year or 2,000 hours of lamp life

*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.



HDMI

PEAK
CONFERENCE
www.PeakConference.com



BenQ America Corp.
www.BenQ.us

BenQ is a registered trademark of BenQ Corp. All rights reserved. Product names, logos, brands, and other trademarks featured or referred to in this material are the property of their respective trademark holders. Specifications subject to change without notice.
TH670 090115_BQus



Because it matters