

logitech

ENABLE EVERY ROOM. ENABLE EVERY PERSON.



Logitech® ConferenceCam CC3000e

The Logitech® ConferenceCam CC3000e combines breakthrough affordability and professional audio and video to turn any meeting space into a video-enabled collaboration place. By using your familiar computing environment and VC application of choice, the CC3000e is plug-and-play and easy to deploy. Workgroups of 6-10 people can now experience the productivity benefits of crystal-clear face-to-face communication.



BlueJeans

lifesize

zoom



broadsoft



Logitech ConferenceCam CC3000e

VIDEO

HD 1080p video quality at 30 frames-per-second
Brings life-like full HD video to conference calls, enabling expressions, non-verbal cues and movements to be seen clearly.

H.264 UVC 1.5 with Scalable Video Coding (SVC)
Frees up PC bandwidth by putting video processing within the camera, adjusting dynamically to the available bitstream. The result is a smoother video stream in applications like Microsoft® Lync™ 2013.

90-degree field of view with mechanical 260-degree pan and 130-degree tilt
The generously wide field of view and silky smooth pan and tilt controls enhance collaboration by making it easy to see everyone in the room.

10x lossless zoom
Zero in on close-ups of objects and whiteboard content with outstanding detail and clarity.

ZEISS® lens certified
High-precision lens automatically focuses on people and objects to deliver razor-sharp resolution wherever the lens is pointed.

Far-end camera control
Operate camera pan, tilt and zoom functions of another Logitech ConferenceCam in the remote location.¹

AUDIO

Omni-directional full duplex mics
Conference participants can clearly converse from a 20-foot diameter around the base, making it seem like conversations are happening in the same room.

Acoustic echo cancellation and noise-cancelling
Optimized to hear and be heard even in noisy environments.

Wideband audio supporting stereo or mono audio modes
True wideband audio enables people on both sides of the call to enjoy a life-like communication experience.

Touch controls
Provide excellent response for call answer/end², volume, mute and other functions without transmitting audible noise through the audio path.

LCD displays Caller ID and other info
View call-related info² (caller ID, call duration, etc.) and speakerphone/camera function indicators (volume control, etc.) on LCD display screen.

Dockable remote control
Operate camera pan, tilt and zoom, volume up/down and answer/hang-up² functions on the base console or with remote control that docks in console when not in use.

CONNECTIVITY AND USAGE

Compatible with Mac® and PC
Employees simply connect a laptop of their choice to conduct life-like meetings within their own familiar computing environment.

USB video/audio connectivity and Bluetooth® audio connectivity with NFC (Near Field Communication) pairing³
USB plug-and-play connectivity makes set-up with a laptop or thin client simple, or connect to a Bluetooth® device for professional audio calls. Easily pair NFC-enabled mobile devices to the CC3000e by simply touching them together.

Optimized for Microsoft® Lync™, Cisco® compatible* (with Jabber® and Webex®), works with Skype™, integrated with Vido™
Broad application compatibility ensures an integrated experience with most business-grade VC platforms.

Camera "Home" preset
User-defined preset returns camera to preferred viewing position upon wake-up.

Visual call status indicator
Onboard LEDs flash to provide a visual alerts and call status.

Kensington Security Slot
Camera and speakerphone are each provisioned with Kensington Security Slots to help secure the equipment with anti-theft locks.

TECH SPECIFICATIONS

CAMERA

Smooth motorized pan, tilt and zoom, controlled from remote or console
260-degree pan, 130-degree tilt
10X lossless zoom
90-degree Field of View
Full HD 1080p 30fps with onboard H.264 UVC 1.5 encoding
Camera "Home" preset key
Far-end control (PTZ) of ConferenceCam products
ZEISS® Optics with autofocus
Kensington Security Slot
LED to confirm video streaming
Standard tripod thread

SPEAKERPHONE

LEDs for speakerphone streaming, mute, hold, and Bluetooth® pairing
Microphones (Tx)
Two omni-directional microphones supporting 20-foot diameter range
Frequency response: 100Hz - 7.75KHz
Sensitivity: -28dB +/- 3dB
Distortion: <1% @ 1KHz at 65dB
Speakers (Rx)
Frequency response: 120Hz - 10KHz
Sensitivity: 83dB SPL +/- 3dB at 1W/1M
Max output: 95dB SPL
Distortion: <5% from 200Hz
Kensington Security Slot

REMOTE CONTROL

Dockable remote control for all available functions
10-foot range remote control

HUB/CABLE

Central mountable hub for connection of all components
Included adhesive solution for under-table mounting
Two 16-foot cables for connection between hub and camera/speakerphone
One 10-foot USB cable for connection to PC/Mac
AC Power adapter

COMPLIANCE AND TOOLS

USB 2.0 compliant
UVC-compliant video and audio for broad application compatibility
Optimized for Microsoft® Lync™, Cisco® compatible,⁴ works with Skype™, integrated with Vido™
Downloadable diagnostic tool
Field upgradeable firmware tool for PC or Mac
Downloadable app plug-ins for advanced feature support for PC or Mac

PRODUCT SPECIFICATIONS

ConferenceCam CC3000e

Part #: 960-000982
UPC Code: 097855102096

SYSTEM REQUIREMENTS

Windows® 7 or 8
Mac OS® X 10.7 or higher
Google Chromebook Version 29.0.1547.70,
Platform 4319.79.0
For full HD support, please check with your software application provider for system requirements.

PRODUCT DIMENSIONS + WEIGHT

Camera	Remote
130 x 130 x 150 mm 5.12 x 5.12 x 5.91" 590g/20.81oz	50 x 120 x 9.8 mm 1.97 x 4.72 x 0.36" 48g/1.69oz
Speakerphone	Package
240 x 240 x 68 mm 9.45 x 9.45 x 2.68" 810g/28.57oz	500 x 145 x 300 mm 19.69 x 5.71 x 12.13" 3590g/126.63oz
Hub	Wall/Table Mount
95 x 74 x 34 mm 3.74 x 2.91 x 1.34" 50g/1.76oz	210 x 120 x 99 mm 8.27 x 4.72 x 3.90" 255g/8.99oz

INSIDE THE BOX

Speakerphone, Camera, Remote Control, Powered Hub, Wall/Table Mount, Two 16-foot cables for Speakerphone/Hub and Camera/Hub Connection, USB cable for Hub/PC connection, Adhesive solution for hub mounting, power adapter, Quick Start Guide.

WARRANTY

2-year limited hardware

¹ With Skype for Business, Microsoft® Lync™ and Vido deployments; Lync requires plug-in download.

² With Skype for Business, Microsoft® Lync™, Skype™, Cisco Jabber™ and Vido deployments

³ With NFC-enabled mobile devices

⁴ See www.logitech.com/ciscocompatibility for the latest version.