

GM 5923/5924 Gooseneck Microphones

G

GM 5923/5924 Gooseneck Microphones

- Gooseneck microphones
- · Excellent sound quality
- Two lengths, 40 cm and 50 cm
- Small diameter
- · LED indication in microphone head

Description

The GM 5923/5924 gooseneck microphones are a new range of gooseneck microphones in the DDS 5900 System.

The small-diameter gooseneck design permits highly flexible positioning while maintaining a smooth, well-contoured appearance.

The GM 5923/5924 are designed for clear, highly intelligible sound reinforcement.

Features

The GM 5923/5924 have the following standard features:

- Condenser gooseneck microphones
- Cardiod polar pattern
- Small-diameter microphone capsule
- · High-quality sound reinforcement
- · Flexible gooseneck
- XLR connector
- · LED lightring indication in microphone head
- High close talk SPL level
- Low noise level



Specifications

How To Order

Electrical

Transducer type	Condenser
Polar pattern	Cardiod
Frequency response	30 Hz - 18 kHz
Sensitivity	-52 +/- 3dB(0dB = 1V/1Pa, 1 kHz)
Maximum input sound level	110 dB SPL, 1 kHz at 3% THD
Signal-to-noise ratio	>60 dBA
Front/back ratio	>25 dB (1 kHz)

Connectors

Connector type 3-pin male XLR

Mechanical

Color Black

Gooseneck Microphones

GM 5923, 40 cm	18 12 05910
GM 5924, 50 cm	18 12 05920



PERFORMANCE

Shure Incorporated 5800 West Touhy Avenue Niles, IL 60714-4608 USA Tel. +1 847 600 2000 Fax +1 847 600 1212 (USA) Fax +1 847 600 6446

Fax +1 847 600 1212 Fax +1 847 600 6446 info@shure.com



Danish Interpretation

Systems A/S Vestre Teglgade 12 DK-2450 Copenhagen SV Denmark Tel. +45 33 85 40 40 Fax +45 33 85 40 41 salessupport@dis.cc

DIS Middle East

LOB 15; Office 221 Jebel-Ali Free Zone P.O. Box 17343 UAE Tel. +971 4 88 71 915 Fax +971 4 88 71 897 dubai@dis.cc

DIS Asia Pacific

1497 Soi Latphrao 94 (Town in town 3/2) Latphrao Rd., Plubpla Wongtonglang Bangkok 10310 Thailand Tel. +662 559 3420 Fax +662 559 3424 bangkok@dis.cc

Data subject to change without notice.