

LightStream™ XGA 1024 x 768 Networkable Projector

True-to-Life Color + Smart Design



PJD6352



Featuring true-to-life color and a smart design, the ViewSonic® LightStream PJD6352 networkable projector makes the grade in any classroom, and helps corporate users rise to the top in any boardroom. Equipped with an exclusive SuperColor™ technology and a high-brightness output, this projector strikes a perfect balance of color and light to deliver the ultimate in color accuracy without compromise. A smart and intuitive design includes PortAll™—a hidden MHL/HDMI port perfect for wireless dongles that let you wirelessly stream multimedia content from a mobile device, or notebook PC, to the projector. What's more, with a wider optical zoom as well as horizontal and vertical keystone correction, this projector provides for flexible setup. Equipped with an easy-to-use network management system that lets you remotely control over 250 LightStream projectors, the PJD6352 is great for use in multiple classrooms across an entire campus, or multiple meeting rooms in an office building.

Key Features:

- Best in class color accuracy
- Secure MHL/HDMI port
- Network capable
- Smart design
- Enhanced sound

Designed for:

- Education
- Business

LightStream™ XGA 1024 x 768 Networkable Projector

PJD6352

| Projection Distance | | Screen Size (4:3) Diagonal | |
|---------------------|----------|-------------------------------|--------|
| Inches | Meters | Inches | Meters |
| 36-47 | 0.9-1.2 | 30 | 0.8 |
| 48-63 | 1.2-1.6 | 40 | 1.0 |
| 73-94 | 1.8-2.4 | 60 | 1.5 |
| 97-126 | 2.5-3.2 | 80 | 2.0 |
| 121-157 | 3.1-4.0 | 100 | 2.5 |
| 182-236 | 4.6-6.0 | 150 | 3.8 |
| 242-315 | 6.2-8.0 | 200 | 5.1 |
| 303-394 | 7.7-10.0 | 250 | 6.4 |
| 363-472 | 9.2-12.0 | 300 | 7.6 |



Specifications

| | | |
|----------------------|--------------------|--|
| DISPLAY | Type | 0.55" Digital Micromirror Device (DLP™) |
| | Resolution | 1024 x 768 (native) |
| | Lens | 1.3x manual optical zoom / manual optical focus |
| | Keystone | Vertical (± 30°) / Horizontal (± 30°) |
| | Size | 30 – 300 in. / 0.76 – 7.62 m (diagonal) |
| | Throw Distance | 3.28 – 32.8 ft. / 1.0 – 10.0 m |
| | Throw Ratio | 1.51~1.97:1 |
| | Lamp | 210 watt |
| | Light Life | 4000 / 10000* (Normal / Eco-mode) |
| | Brightness | 3500 lm |
| | Contrast Ratio | 22,000:1 (DynamicEco mode) |
| | Aspect Ratio | 4:3 (native) |
| | Color Depth | 30 bits, 1.07B Color (10+10+10) |
| INPUT SIGNAL | Computer and Video | NTSC M(3.58MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SECAM (B, D, G, L, L1), SD 480i and 576i, ED 480p and 576p, HD 720p, 1080i, 1080p |
| | Frequency | Fh: 15–102KHz, Fv: 23–120Hz |
| COMPATIBILITY | PC | Up to 1920x1080 |
| | Mac® | Up to 1920x1080 (may require MAC adapter) |
| CONNECTOR | Digital Input | HDMI 1.4 (x1) / HDMI/MHL (x1) |
| | RGB Input | 15-pin mini D-Sub (x2) |
| | Composite Input | RCA jack (x1) |
| | Audio In | 3.5mm mini jack (x2) |
| | Audio Out | 3.5mm mini jack (x1) |
| | Video Out | 15-pin mini D-Sub (x1) |
| | USB | Mini type B (mouse control and maintenance) |
| | LAN | RJ45 |
| | Control | RS232 |

| | | |
|-------------------------------|--|--|
| AUDIO | Speaker | 10W (x1) |
| NOISE LEVEL | Normal / Eco-mode | 32 dB / 27 dB |
| POWER | Voltage | 100–240VAC (Auto Switching), 50-60Hz (universal) |
| | Consumption | 330W (max) / <0.5W (stand-by mode) |
| CONTROLS | Basic | Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source |
| | OSD | Display, Picture, Source, System Setup (Basic), System Setup (Advanced), Information (See user guide for full OSD functionality) |
| OPERATING CONDITIONS | Temperature | 32–104° F (0–40° C) |
| | Humidity | 10–90% (non-condensing) |
| | Altitude | 0–6000 ft (1828.8m) |
| DIMENSIONS (W x H x D) | Physical | 12.44 x 4.08 x 8.98 in. / 316 x 103.7 x 228 mm |
| | Packaging | 16.0 x 17.72 x 8.85 in. / 410 x 450 x 225 mm |
| WEIGHT | Net | 5.1 lb. / 2.3 kg |
| | Gross | 8.8 lb. / 4.0 kg |
| REGULATIONS | CB, TUV-GS, UL/cUL, FCC (including ICES-003), CE, C-Tick Mexico Energy test/Registration, EAC, UkrSEPRO/EMC DOC, UL COC, TUV-S Mark (Argentina), PSB, KCC, KC, SASO, CCC, WEEE, RoHS, REACH, SVHC, ErP | |
| WARRANTY | 3-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service** | |

Optional Accessories (Sold Separately)

| | |
|---|-------------|
| Wireless Presentation Gateway Dongle..... | WPG-300 |
| Wireless Presentation Gateway | WPG-370 |
| 3D Active Shutter Glasses..... | PGD-350 |
| Universal Ceiling Mount..... | PJ-WMK-006 |
| Carrying Case..... | PJ-CASE-008 |
| Replacement Lamp | RLC-097 |
| Cable Management | PJ-CM-004 |

What's in the box?

PJD6352 projector, power cable, VGA cable, remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide), cable management



*Lamp life may vary based on actual usage and other factors. **One year Express Exchange® service requires product registration. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies, DLP® and DLP logo are registered trademarks of Texas Instruments. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Copyright © 2016 ViewSonic Corporation. All rights reserved. [18401-00B-01/16]

www.viewsonic.com